








岩土支护







山东洛克曼钻具有限公司

洛克曼锚杆系统适用于几乎所有的地面条件。应用范围包括地下采矿和隧道、公路和铁路隧道、淡水隧道、水电站、民用和军用建筑、微桩等

RT20, R25, R32, R38, T38, R51, R76, T76, ... 螺纹连接钻头

钻头	水孔		合金		斜度	尺寸	
	MM		MM			D	
球齿钻头	Front	Gauge	Front	Gauge	Front	mm	
	No Size	No Size	No Size	No Size			
	1x7	2x7	1x9	4x9	35°	40	
	1x7	2x7	1x9	4x9	35 °	42	
	2x8	2x8	2x9	4x9	35 °	45	
	2x8	2x8	2x9	4x9	35 °	50	
	2x9	2x8	3x9	4x9	35 °	55	
	2x9	2x8	3x9	4x9	35 °	60	
	2x10	2x8	4x9	4x9	35 °	65	
	2x10	2x9	4x9	4x10	35 °	70	
	2x11	2x9	4x9	4x10	35 °	75	
	3x11	2x10	7x9	5x10	40 °	80	
	2x13	3x11	5x9	9x10	40 °	110	
	3x13	3x12	6x10	10x10	40 °	115	
	3x14	3x12	6x10	12x10	40 °	120	
		3x10	3x9	6x9	35°	76	
	1x11	2x10	4x9	6x9	35°	76	
	1x12	2x10	4x9	6x9	40°	90	
	2x14	2x12	12x9	8x9		150	
	2x14	2x12	14x9	8x9		162	
	2x16	2x14	16x9	8x10		175	
	2x18	2x16	22x9	12x10		225	

钢齿							
						42	
						45	
						51	
						76	
						96	
						110	
						115	
						150	
十字钻头							
	1x8	2x7				45	
	1x9	2x8				50	
	1x10	4x8				55	
	1x10	4x8				60	
	1x12	4x8				65	
	1x12	4x9				70	
						96	
						115	
						175	
连接套						L mm	
						190	
						235	

锚杆参数

型号	外径 mm	内径 mm	抗拉强度 KN	屈服强度 KN	重量 Kg/m
R25N	25	12	200	150	2.3
R32L	32	20.5	210	160	2.9
R32N/1	32	20.5	280	230	2.9
R32N	32	18	280	280	3.5
R32S	32	15	360	280	4.1
R38N	38	19	500	400	5

R51L	51	36	550	450	7
R51N	51	33	800	630	8.5
T30/14	30	14	260	220	2.9
T40/16	40	18	660	525	7
T76/45	76	45	1900	1500	19.7
T103/51	103	51	3460	2750	43.4
T127/103	127	103	2320	2010	28.7

